

Boomlift / Manlift

Used Boom Lift Fontana - One of the commonest types of industrial equipment and aerial equipment is the boom lift. Also referred to as elevating work platforms, aerial devices, cherry pickers, mobile elevating work platforms and aerial work platforms, boom lifts are capable of completing jobs at higher elevations easily and efficiently. Many industries rely on boom lifts every day including retail locations, construction contractors, companies and warehouses. Staying safe while working at high altitude is essential for daily success. The material handling industry offers many boom lift models. A single operator can control a variety of boom lift models. This equipment became popular in the orchard industry to harvest fruit without having to climb a ladder and balance heavy baskets or pails. It can be difficult to secure a ladder on farmland or in orchard settings. Boom lifts make it much easier to reach high tree tops for collecting fruit. Gaining Access Over Obstacles Some boom lift models can move up and over obstacles, making them ideal for working over top of items safely and efficiently. Boom lifts can reach items even when it is impossible to move the machine right underneath the area you are working in, making it possible to fix overhead cables within telephone line and pole installation, window cleaning applications and similar circumstances. The articulated boom lift is an example that has numerous joints enabling it to bend over or under items. These sections can independently move to allow workers to gain access to a variety of places. This equipment is popular in narrow storage locations and hallways thanks to its' tight turning radius. There are dual-fuel models that can work inside and outside; diesel is best utilized outside while interior locations rely on electric models. Articulating Boom Lifts Popular for maintenance jobs and construction, articulating boom lifts are a useful piece of material handling equipment. They provide a vital piece to the fleet for servicing power lines and overhead wires. Certain models are outfitted with water cannons to be used in firefighting applications. Maximum reach can be attained with telescoping boom sections on certain models. Some articulating boom lift models have an extra jib to enable their platform to reach six feet further in any direction. These boom lifts go by the nickname of "spiders," since their legs can support the entire machine on steep or difficult terrain. Smaller units called interior articulating boom lifts are capable of fitting through doorways, making them valuable in retail, warehousing and storage facilities. Electric boom lifts are common for interior jobs due to their quieter options and lack of unhealthy carbon monoxide exhaust. Telescopic Boom Lifts Telescopic boom lifts do not bend the way articulating boom lifts do. These units use hydraulics to retract and extend outwards and upwards. The operator who is situated in the platform has the controls to operate and extend the lift on their own. Some taller and larger models have a jib situated near the top that is similar to an articulating boom lift model. Boom lifts are available that reach higher than one-hundred and eighty feet. These machines are built to be stable and reliable. Some are able to extend to their full height capacity in less than 60 seconds. Adjustable speed, along with varying weight range capacities from 500 to 1000 lbs. are available in dual-fuel and diesel options. Available in 4WD and the ability to fit through small spaces. Telescopic booms are common in a variety of settings due to their ability to combine height and reach. Jib Certain boom lift models have a jib or an extension located between the platform and the end of the main boom. This enables extra reach and another articulation point or hinge for the platform to move side-to-side or up-and-down. Articulating boom lifts and telescoping boom lifts may have jibs. Articulating models have a joint situated roughly halfway between the wheels and the platform to enable it to reach over an obstacle and then lower again if required. Genie Articulating Boom Lifts The Genie Z-boom model is a common kind of articulating boom lift that can be found on the market. This unit offers exceptional versatility for accessing difficult to reach locations with the capacity to lift up, over and out with precision. The first Genie Z-30/20 articulating Z-boom model was launched in 1985. Thanks to their "up an over" abilities, they have gained the ultimate popularity that continues today. Proper Safety Measures Of course, safety is the highest priority when operating any type of boom lift. Safety hazards must be advertised to everyone who is working in the area for

best practices. Safe operation of the machine and personal safety must be paramount. Before operating the machine, effective communication and essential safety gear need to be in place. Prior to operating, ensure there are no open flames, combustible or flammable items, lit cigarettes, battery gases or engine fuels present. It is important to have an accessible, securely mounted and visible fire extinguisher mounted within the operators' reach. Maintaining a clear area around charging stations and work surfaces is important as tools or clutter could damage the boom lift or cause tire punctures etc. Daily Maintenance Before engaging in activity, it is vital to do a visual inspection and consult the maintenance records to make sure all items are up to date and safe prior to operation. These industrial machines rely on lifting and supportive mechanisms to stabilize the weight. Straps, fasteners and chains need to be checked they are in good condition. It is very dangerous to reuse single use fasteners and other components as they might fail if used beyond their recommendations. Discarded solvents and oils must be disposed of safely and in an approved container to prevent environmental contamination. Workbenches and workshop or garage areas need to have adequate lighting and ventilation. Maintenance is broad and typically categorized into subsections including Quarterly Maintenance, Annual Maintenance, Commissioning and Programmed Maintenance Intervals. Maintenance Inspection Report Main aspects of the boom lift are categorized and divided to facilitate the inspection process. Common maintenance categories include Control and Function, Turntable, Booms, Platform, Drive Chassis and Engine. Not complying with routine maintenance can put the operator at a huge safety risk, lead to damaged components, terrible performance and preventable downtime. The maintenance inspection report extend the performance and service life of the machine and needs to be accurately maintained to ensure the machine is safe to run and that the machine is capable of performing properly. Commissioning refers to a list of one-time maintenance procedures to be complete at 50 hours and at 150 hour intervals. Annual and Quarterly maintenance procedures need to be performed once or multiple times a year. There are a variety of programmed maintenance procedures based on preparing the machine for pre-delivery machine operating. Set yourself up for success by consulting your maintenance manual before operating the equipment to ensure battery life, oil changes and fluid levels are ready to go.